Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1AV1104A **SIMOTICS GP - 100 L - IM B3 - 2p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
230	Δ	50	3.00	-/-	10.60	2835	10.1	81.5	83.2	82.7	0.87	0.82	0.73	6.4	3.2	3.5	IE1
400	Y	50	3.00	-/-	6.10	2835	10.1	81.5	83.2	82.7	0.87	0.82	0.73	6.4	3.2	3.5	IE1
460	Y	60	3.45	-/-	5.80	3435	9.6	84.5	85.5	85.2	0.88	0.84	0.75	7.4	3.9	3.9	IE1

IM B3 / IM 1001	FS 100 L	20 kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN

Environmental conditions : -20 °C - +40 °C / 1,000 m

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	67.0 / 79.0 dB(A) 2)	71.0 / 83.0 dB(A) 2)
Moment of inertia	0.0034 kg m²	
Bearing DE | NDE	6206 2Z C3	6206 2Z C3
bearing lifetime		
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h
Lubricants	Unirex N3	
Regreasing device	No	
Grease nipple	-/-	
Type of bearing	Preloaded bearing DE	
Condensate drainage holes	No	

External earthing terminal	No
Vibration severity grade	A
Insulation	155(F) to 130(B)
Duty type	S1
Direction of rotation	bidirectional
Frame material	aluminum
Coating (paint finish)	Standard paint finish C2
Color, paint shade	RAL7030
Motor protection	(A) without (Standard)
Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4.0 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11.0 mm - 21.0 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

آبادیزل نمایندگی فروش الکتروموتور زیمنس

تهران - خیابان سعدی جنوبی مجتمع
تجاری اداری سعدی - طبقه ۴ - واحد ۴۱۲
۰۹۱۲۷۶۳۱۳۸۷ ۰۲۱-۳۳۹۹۲۲۹۴
۰۹۱۲۴۴۵۵۷۹۳ ۰۲۱-۳۳۹۱۴۰۸۴

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	
DI MC LVM		DT Configurator		*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*

SIEMENS

document type	document status	customer
datasheet	released	
title	document number	
1LE1002-1AA42-2AA4		

rev.	creation date	language	Page
01	2020-12-31 16:55	en	1/1

© Siemens AG 2020