

DATA SHEET

Synchronous Alternator



Customer		Notes:
Customer reference		
Product line	: AG10-250S110AI	Product code : 14418535
Area classification	: Safe	1010264379

General data		Degree of protection	: IP23
Frame (IEC)	: 250	Mounting style	: B15T
Insulation Class	: 180°C (H)	Number of poles	: 4
Total Harmonic Distortion (no load)	: ≤ 3%	Type of Pole	: Salient
Stator winding pitch	: 2/3	Nominal rotation - 50 Hz	: 1500 rpm
Altitude	: up to 1000 m.a.s.l	Nominal rotation - 60 Hz	: 1800 rpm
Number of Leads	: 12	Overspeed	: 2250 rpm
Power factor	: 0.8 to 1.0	Alternator mass	: 644 kg
Excitation system	: Brushless with Auxiliary Coil	Overload	: 1.1x In per 1h each 6h
Cooling	: IC01	Momentary Overload	: 1.5x In per 30s

Frequency and number of phases		50 Hz				60 Hz													
		3ph		1ph	3ph		1ph												
Voltages (V)	Y connection	380	400	415	-	380	416	440	480	-									
	YY connection	190	200	208	-	190	208	220	240	-									
	Δ connection	220	230	239	-	220	240	254	277	-									
	ΔΔ connection	110	115	120	-	110	120	127	138	-									
	Zig-zag or single phase delta	-	-	-	190 - 200	-	-	-	-	220 - 240									
Output power (kVA)	ΔT=80°C (Ta=40°C)	168	168	159	97.0	168	180	186	208	108.0									
	ΔT=105°C (Ta=40°C)	192	192	182	110.9	190	206	217	238	125.0									
	ΔT=125°C (Ta=40°C)	210	210	199	121.2	210	225	233	260	135.0									
	ΔT=150°C (Ta=40°C)	230	230	218	132.8	230	246	250	290	144.0									
	ΔT=163°C (Ta=27°C)	240	240	228	138.6	240	255	260	295	150.0									
Electrical data (FP=0.8 / ΔT=125°C / Ta=40°C)	Xd(%) Dir. axis synchronous reactance	479.6	390.2	338.3	639.43	571.4	487.0	456.8	414.55	609.11									
	X'd(%) Dir. axis transient reactance	18.3	14.9	12.9	24.4	21.8	18.6	17.4	15.82	23.24									
	X''d(%) Dir. axis subtrans. reactance	13.1	10.7	9.3	17.5	15.6	13.3	12.4	11.26	16.6									
	Xq(%) Quad. axis sync. reactance	132.6	107.9	93.5	176.82	158.0	134.7	126.3	114.63	168.43									
	X''q(%) Quad. axis subtrans. react.	10.5	8.5	7.4	14.0	12.5	23.2	10.0	9.01	13.28									
	X2(%) Negative sequence reactance	17.1	13.9	12.1	22.82	20.4	18.2	16.3	14.75	21.71									
	X0(%) Zero sequence reactance	2.2	1.8	1.5	2.92	2.6	2.2	2.1	1.88	2.77									
	T'd(ms) Short Circ. Trans. time const.	66.1	53.8	45.2	88.18	78.8	64.2	63.0	57.17	84.0									
	T''d(ms) Short Circ. Sub. time const.	1.7	1.4	1.2	2.32	2.1	1.7	1.7	1.5	2.21									
	T''do(ms) Open Circ. time const Trans	1319	1073	901	1758.45	1571	1281	1256	1140.03	1675.07									
	T''do(ms) Open Circ. time const Subt	2.4	1.9	1.6	3.18	2.8	2.3	2.3	2.06	3.03									
	Ta(ms) Armature time const.	11	9	7	14.59	13	11	10	9.46	13.9									
	uc(V) Full load excitation voltage	49.3	46.9	49.7	49.29	37.3	42.9	38.7	41.64	38.66									
	ic(A) Full load excitation current	4.0	3.9	4.1	4.05	3.1	3.5	3.2	3.42	3.18									
ic(A) No load excitation current	0.7	0.8	0.8	0.88	0.5	0.7	0.7	0.76	0.88										
Icc(A) Sustained Short-Circ. Current	957	909	831	909.33	957	943	917	938.19	843.75										
Kcc Short-circuit ratio	0.43	0.35	0.3	0.58	0.52	0.45	0.41	0.37	0.55										
Efficiency (%)	Power factor	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0		
	25% of load	91.2	93	91.4	93.2	91.9	93.8	83.9	85.6	91.4	93.1	91.4	93.1	91.4	93.1	91.3	93.1	84.1	85.6
	50% of load	92.7	94.4	92.8	94.5	93.4	95.1	85.2	86.8	92.9	94.5	93.1	94.6	93.2	94.7	93.2	94.8	85.8	87.2
	75% of load	92.2	94.2	92.5	94.4	93.1	95	84.8	86.6	92.6	94.3	92.8	94.5	93.1	94.7	93.1	94.8	85.6	87.1
	100% of load	91.4	93.5	91.8	93.9	92.4	94.4	84	86	91.7	93.7	92.1	94	92.4	94.3	92.6	94.4	85	86.7
	125% of load	90.2	92.6	90.9	93.2	91.5	93.8	80.8	83.4	90.7	93	91.2	93.4	91.5	93.6	91.9	93.9	84.2	86.1

Other characteristics		Automatic voltage regulator		According to:	
Air flow	: 1.16 m³/s	Accuracy (stability)	: +/- 0.5%	IEC 60034	
Exciter stator winding resistance at 20°C	: 12.17 ohm	Rated current	: 5 A	NBR 5117	
Stator winding resistance at 20°C	: 0.02664 ohm	Analog input	: Yes	NEMA MG1	
Rotor winding resistance	: 1.5 ohm	Digital input	: No	VDE530	
Stator winding layers	: 2	Peak current	: 7 A/10 s	ISO 8528	
Inertia WR²	: 2.37 kgm²	Droop / TC	: Yes	CSA	
NDE Bearing	: 6314 2RS	Dynamic recovery	: 8 to 500 ms		
DE bearing		U/F	: Yes		
Flange	: SAE 1	Internal voltage adjustment	: +/- 15%		
Coupling disc	: SAE 14	External voltage adjustment	: +/- 10%		
		Transient recovery time for ΔU=20%	: 500 ms		

Rev.	Changes Summary				Performed		Checked		Date	
Performed by										
Checked by										
Date							Page		Revision	
							1 /			