

DATA SHEET

Synchronous Alternator



Customer	:	Notes:
Customer reference	:	
Product line	: AG10-280MI20AI	Product code : 14418826
Area classification	: Safe	1010268256

General data Frame (IEC) : 280 Insulation Class : 180°C (H) Total Harmonic Distortion (no load) : ≤ 3% Stator winding pitch : 2/3 Altitude : up to 1000 m.a.s.l Number of Leads : 12 Power factor : 0.8 to 1.0 Excitation system : Brushless with Auxiliary Coil Cooling : IC01	Degree of protection : IP23 Mounting style : B15T Number of poles : 4 Type of Pole : Salient Nominal rotation - 50 Hz : 1500 rpm Nominal rotation - 60 Hz : 1800 rpm Overspeed : 2250 rpm Alternator mass : 1068 kg Overload : 1.1x In per 1h each 6h Momentary Overload : 1.5x In per 30s
---	---

Frequency and number of phases		50 Hz				60 Hz							
		3ph			1ph	3ph				1ph			
Voltages (V)	Y connection	380	400	415	-	380	416	440	480	-	-	-	-
	YY connection	190	200	208	-	190	208	220	240	-	-	-	-
	Δ connection	220	230	239	-	220	240	254	277	-	-	-	-
	ΔΔ connection	110	115	120	-	110	120	127	138	-	-	-	-
	Zig-zag or single phase delta	-	-	-	190 - 200	-	-	-	-	-	-	-	220 - 240
Output power (kVA)	ΔT=80°C (Ta=40°C)	320	328	311	185	336	362	380	412	219	-	-	-
	ΔT=105°C (Ta=40°C)	367	376	357	212	395	414	440	472	254	-	-	-
	ΔT=125°C (Ta=40°C)	400	410	389	231	420	452	475	515	274	-	-	-
	ΔT=150°C (Ta=40°C)	430	450	427	248	450	486	515	550	297	-	-	-
	ΔT=163°C (Ta=27°C)	450	470	446	260	468	506	533	580	308	-	-	-
Electrical data (FP=0.8 / ΔT=125°C / Ta=40°C)	Xd(%) Dir. axis synchronous reactance	318.1	270.0	256.5	424.2	429.0	360.1	338.0	292.35	450.7	-	-	-
	X'd(%) Dir. axis transient reactance	16.4	14.8	14.1	21.9	21.6	17.6	16.5	14.91	22.0	-	-	-
	X''d(%) Dir. axis subtrans. reactance	11.8	10.7	10.1	15.7	15.6	12.7	11.9	10.71	15.9	-	-	-
	Xq(%) Quad. axis sync. reactance	85.0	76.9	73.1	113.3	136.6	0.0	92.9	104.45	123.9	-	-	-
	X''q(%) Quad. axis subtrans. react.	9.4	8.4	8.0	12.6	12.5	22.0	9.5	11.7	12.7	-	-	-
	X2(%) Negative sequence reactance	10.6	9.5	9.0	14.2	14.1	17.4	10.7	11.2	14.3	-	-	-
	X0(%) Zero sequence reactance	2.0	1.8	1.7	2.6	2.6	2.1	2.0	1.79	2.6	-	-	-
	T'd(ms) Short Circ.Trans.time const.	110.0	136.0	136.0	146.7	138.0	78.1	137.0	134.03	182.7	-	-	-
	T'd(ms) Short Circ. Sub. time const.	11.0	1.4	1.4	14.7	2.1	1.6	1.4	1.2	1.8	-	-	-
	T'do(ms) Open Circ. time const Trans	1584	1951	1951	2112	2102	1030	1998	1874.47	2664	-	-	-
	T'do(ms) Open Circ. time const Subt	1.7	2.1	2.1	2.3	2.6	2.0	2.0	2.11	2.7	-	-	-
	Ta(ms) Armature time const.	14	13	13	19	19	14	15	13.09	19	-	-	-
	uc(V) Full load excitation voltage	60.1	61.6	61.6	60.1	50.5	55.9	53.4	56.66	53.4	-	-	-
	ic(A) Full load excitation current	2.9	3.0	3.0	2.9	2.4	2.7	2.6	2.72	2.6	-	-	-
	ic(A) No load excitation current	0.8	0.9	0.9	1.0	0.6	0.7	0.7	0.8	0.9	-	-	-
Efficiency (%)	Icc(A) Sustained Short-Circ. Current	1823	1775	1624	1732	1914	1855	1870	1858.35	1714	-	-	-
	Kcc Short-circuit ratio	0.31	0.35	0.39	0.41	0.25	0.27	0.29	0.33	0.39	-	-	-
	Power factor	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0
	25% of load	91.1	93	90.8	92.7	90.8	92.7	83.8	85.6	92.3	94	92.1	93.8
	50% of load	93.8	95.3	93.7	95.2	93.7	95.2	86.3	87.6	94.4	95.7	94.3	95.5
	75% of load	94.1	95.6	94.1	95.6	94.1	95.6	86.5	87.9	94.5	95.8	94.6	95.9
	100% of load	93.8	95.4	93.9	95.5	93.9	95.5	86.3	87.7	94	95.4	94.3	95.7
	125% of load	93.2	94.9	93.4	95.2	93.4	95.2	85.8	87.3	93.4	94.9	93.7	95.2
		94	95.5	94	95.5	94	95.5	87.3	88.4	94.9	95.5	94	95.5
		95.2	96.1	95.2	96.1	95.2	96.1	88.4	89.5	95.2	96.1	95.2	96.1
		96.1	97.1	96.1	97.1	96.1	97.1	89.5	90.6	96.1	97.1	96.1	97.1
		97.1	98.1	97.1	98.1	97.1	98.1	90.6	91.7	97.1	98.1	97.1	98.1
		98.1	99.1	98.1	99.1	98.1	99.1	91.7	92.8	98.1	99.1	98.1	99.1
		99.1	100	99.1	100	99.1	100	92.8	93.9	99.1	100	99.1	100

Other characteristics Air flow : 2.12 m³/s Exciter stator winding resistance at 20°C : 20.86 ohm Stator winding resistance at 20°C : 0.0086 ohm Rotor winding resistance : 1.91 ohm Stator winding layers : 2 Inertia WR² : 4.82 kgm² NDE Bearing : 6315 2RS DE bearing : Flange : SAE 1 Coupling disc : SAE 14	Automatic voltage regulator Accuracy (stability) : +/- 0.5% Rated current : 5 A Analog input : Yes Digital input : No Peak current : 7 A/10 s Droop / TC : Yes Dynamic recovery : 8 to 500 ms U/F : Yes Internal voltage adjustment : +/- 15% External voltage adjustment : +/- 10% Transient recovery time for ΔU=20% : 500 ms	According to: IEC 60034 NBR 5117 NEMA MG1 VDE530 ISO 8528 CSA
--	---	--

Rev.	Changes Summary	Performed	Checked	Date
Performed by				Page 1 /
Checked by				
Date	10/08/2022			