| | |
|---|---|
| 宗申动力 ZONG SHEN POWER | **BPB4000** |
| | **4kw Open Frame Inverter Generator** |
| | **Engine: GB** |

| **Appearance** | **BPB4000 4kW Inverter Generator Specs** | |
|---|---|---|
| | Generator Type | **Permanent Magnet** |
| | Alternator Material | **Copper** |
| | Frequency (Hz) | **50** |
| | Voltage (V) | **230** |
| | THD (%) max | **≤ 3** |
| | Max Output (kw) | **3.8** |
| | Rated Output (kw) | **3.5** |
| | Run Time @ 50% load (hrs) | **8** |
| | Fuel Tank Capacity (L) | **11** |
| | Noise (dBA) | **68 ~ 75** |
| | Net Weight (kg) | **34** |
| | Packing Size (cm) | **55 x 37 x 51** |
| | | |
| | | |
| | **Engine** | |
| | **GB225** | |
| | Displacement (cc) | **224** |
| | Bore × stroke (mm) | **72x55** |
| | Oil quantity (cc) | **400 ~ 600** |
| | Recommended oil | **10w-30** |
| | Fuel tank volume (cc) | **n/a** |
| | Starting System | **Recoil** |
| | Ambient temperature（℃） | **5-40** |
| | Rated power (kW/rpm) | **4.5/3600** |
| | Max torque (N • m/rpm) | **12.5/2600** |
| | Fuel type (octane RON) | **91** |
| | Certification | **EPA** |
| | Endurance Validation (h) | **500** |
| | Filter configuration | **Foam Element** |
| | Choke control | **Manual** |
| | Flameout method | **Manual Stop Switch** |
| | Oil alarm | **Y** |
| | | |
| | | |
| | | |
| | | |
| | | |