

Product Specifications for 2206A-E13TAG

US

Metric

Gross Mechanical Output

324-461 kWm

Typical Electrical Output

350-500 kVA (280-400 kWe)

Rated Speed

1500/1800 rpm

Prime

350-400 kVA

Standby

400-450 kVA

Prime

320-350 kWe

Standby

350-400 kWe

Emissions

Fuel Optimised

Number of Cylinders

6 vertical inline

Bore

130 mm

Stroke

157 mm

Displacement

12.5 l

Compression Ratio

16.3:1

Aspiration

Turbocharged and air-to-air charge cooled

Combustion System	Direct injection
Rotation from Flywheel End	Anti-clockwise
Cooling System	Liquid
Aftertreatment	-
Typical Alternator Efficiency	92%
Switchable	Yes
Length	2410 mm
Width	1120 mm
Height	1725 mm
Dry Weight	1478 kg
Note 1	*Final dimensions dependent on selected options
Prime Power	Variable load, Unlimited hours usage with an average load factor of 70% of the published prime power rating over each 24 hour period, A 10% overload is available for 1 hour in every 12 hours of operation.
Standby Power	Variable load, Limited to 500 hours annual usage up to 300 hours of which may be continuous running, No overload is permitted.

2206A-E13TAG Standard Equipment

Air inlet system

Mounted air filter

Cooling system

Gear-driven circulating pump

Mounted belt-driven pusher fan

Radiator incorporating air-to-air charge cooler, (supplied loose)

System designed for ambients up to 50°C (122°F)

Electrical equipment

3 level engine protection system

24 volt starter motor and 24 volt 70 amp alternator with DC output

ECM mounted on engine with wiring looms and sensors

Flywheels and flywheel housing

High inertia flywheel to SAE J620 size 14

SAE 1 flywheel housing

Fuel system

Fuel cooler

Governing to ISO 8528-5 class G2 with isochronous capability

Mechanically actuated electronically controlled unit fuel injectors with full authority electronic control

Replaceable 'Ecoplus' fuel filter elements with primary filter/water separator

Mountings

Front engine mounting bracket

Oil system

Full-flow replaceable 'Ecoplus' filter

Oil cooler integral with filter header

Wet sump with filler and dipstick

Optional equipment

110 volt/240 volt immersion heater

Additional speed sensor

Air filter rain hood

Temperature and pressure sensors for gauges

Tool kit

Twin starters/facility for second starter

