

EP73DE



Europower open generating sets with Kubota water-cooled diesel engines, 3000rpm, 50Hz, 4 stroke

Generator:

| | |
|---|-----------------|
| kVA max.: | 6 |
| kVA cont.: | 5.4 |
| kVA: | 5.4kVA @ 1~230V |
| Amps cont.: | 23A @ 1~230V |
| Dimensions l x w x h: | 105x64x78cm |
| Dry weight: | 183kg |
| Weight incl. oil (+ coolant if water-cooled), excl. fuel: | 190kg |
| Weight incl. oil (+ coolant if water-cooled) + fuel: | 230kg |

www.abadiesel.com

Engine:

| | |
|------------------------|--|
| Brand/Type: | Kubota Z482 E4B-EUP-1 |
| HP max.: | 11.3 |
| Power: | 8.3kW max. (3000rpm), 2-cylinder Diesel, Water-cooled |
| Displacement: | 479cm ³ |
| Consumption @75% load: | 1.8 litres/hour |
| Tank: | 47 litres |
| Autonomy @75% load: | 26.1 hours |
| Noise level: | 78dB(A)@7m (*) |
| EU Emission norm: | Stage V |
| Battery voltage: | 12V |

Alternator:

| | |
|--------------------|---|
| Brand/Type | Sincro EK2LCT - 8kVA SAE5/6.5 230V - brushless |
| Nominal voltage: | 1~230V |
| Frequency: | 50Hz |
| Protection degree: | IP23 |

Generators with * cannot be used outdoors in the EU. For applications of generating sets indoors, or if you want to integrate these generators in vehicles, please contact us.

Version:

- 1 socket 230V - 16A + 1 socket CEE 230V - 32A
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Low oil pressure guard
- Magneto-Stop
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter

www.abadiesel.com