

|  |                           |               |   |   |     |
|--|---------------------------|---------------|---|---|-----|
| <b>Models</b>                          |                           |               | <b>SV2800</b>   |   |     |
| <b>Type</b>                            |                           |               | R-type; 220V(50Hz)<br>S-type; 220V(60Hz)<br>D-type; 110/220V(60Hz)<br>LD-type; 120/240V(60Hz) |   |     |
| <b>Frequency</b>                       |                           | Hz            | 50  | 60  |     |
| <b>Engine</b>                          | Models                    |               | V210  |   |     |
|  | Displacement              | CC            | 212   |   |     |
|  | 3000rpm                   | kW            | 3.0   |   |     |
|  | Type                      |               | Air cooled 4-stroke OHV   |   |     |
|  | Oil Alert System          |               | Yes   |   |     |
| <b>Generator</b>                       | Type                      |               | Self-Exciting, 2-pole, Field Rotating Type  |   |     |
|  | Voltage Regulation System |               | AVR   |   |     |
|  | Output                    | Rated         | kW  | 2.0   | 2.3 |
|  |                           | Maximum       |   | 2.3   | 2.8 |
|  | Rated Voltage             |               | (V)   | 220 (R,S-type),<br>110/220 (D-type),<br>120/240 (LD-type) |     |
|  | DC Output (V-A)           |               | No  |   |     |
|  | Power Factor              |               | COS 1.0   |   |     |
| <b>Others</b>                          |                           | Warning Lamps |   | No  |     |
| Fuel Tank Capacity                     |                           | L             | 20  |   |     |
| Dimensions (mm)<br>*with Battery Guard |                           | L             | 623   |   |     |
|  |                           | W             | 438 (532*)  |   |     |
|  |                           | H             | 491   |   |     |
| Dry Weight                             |                           | kg            | 38 (41)   |   |     |
| Sound Level<br>7m Rated Load           |                           | dB            | 69  | 72  |     |
| Continuous Operating<br>Hours          |                           | h             | 15  | 13  |     |