

| | | | | | |
|--|---------------------------|---------|---|---|-----|
| Models | | | SV3300(S) | | |
| Type | | | R-type; 220V(50Hz) S-type; 220V(60Hz) D-type; 110/220V(60Hz) LD-type; 120/240V(60Hz) | | |
| Frequency | | Hz | 50 | 60 | |
| Engine | Models | | V225 | | |
| | Displacement | | CC | 223 | |
| | 3000rpm | | kW | 3.5 | |
| | Type | | Air cooled 4-stroke OHV | | |
| | Oil Alert System | | Yes | | |
| Generator | Type | | Self-Exciting, 2-pole, Field Rotating Type | | |
| | Voltage Regulation System | | AVR | | |
| | Output | Rated | kW | 2.5 | 2.8 |
| | | Maximum | | 2.9 | 3.3 |
| | Rated Voltage | | (V) | 220 (R,S-type), 110/220 (D-type), 120/240 (LD-type) | |
| | DC Output (V-A) | | No | | |
| | Power Factor | | COS 1.0 | | |
| Warning Lamps | | No | | | |
| Fuel Tank Capacity | | L | 20 | | |
| Dimensions (mm) *with Battery Guard | | L | 623 | | |
| | | W | 438 (532*) | | |
| | | H | 491 | | |
| Dry Weight | | kg | 41 (44) | | |
| Sound Level 7m Rated Load | | dB | 70 | 74 | |
| Continuous Operating Hours | | h | 12 | 10 | |